



DIRUI BF-6500/6800/6880 CHECK ASSAY SHEET

LOT: 2411057
Exp.date: 2025-01-05

+

MODE	Parameter		Level:1					Level:2					Level:3				
			Mean	Limit	Range			Mean	Limit	Range			Mean	Limit	Range		
Open	WBC	10 ⁹ /L	2.50	± 0.50	2.00	-	3.00	8.30	± 1.00	7.30	-	9.30	20.30	± 2.50	17.80	-	22.80
	NEU%	%	63.0	± 12.0	51.0	-	75.0	64.0	± 12.0	52.0	-	76.0	85.5	± 12.0	73.5	-	97.5
	LYM%	%	27.0	± 10.0	17.0	-	37.0	27.0	± 10.0	17.0	-	37.0	11.0	± 9.0	2.0	-	20.0
	MON%	%	7.5	± 7.5	0.0	-	15.0	7.0	± 7.0	0.0	-	14.0	2.0	± 2.0	0.0	-	4.0
	EOS%	%	2.0	± 2.0	0.0	-	4.0	1.5	± 1.5	0.0	-	3.0	1.0	± 1.0	0.0	-	2.0
	BAS%	%	0.5	± 0.5	0.0	-	1.0	0.5	± 0.5	0.0	-	1.0	0.5	± 0.5	0.0	-	1.0
	NEU#	10 ⁹ /L	1.58	± 0.31	1.27	-	1.89	5.31	± 1.00	4.31	-	6.31	17.36	± 2.44	14.92	-	19.80
	LYM#	10 ⁹ /L	0.68	± 0.26	0.42	-	0.94	2.24	± 0.83	1.41	-	3.07	2.23	± 1.83	0.40	-	4.06
	MON#	10 ⁹ /L	0.19	± 0.19	0.00	-	0.38	0.58	± 0.58	0.00	-	1.16	0.41	± 0.41	0.00	-	0.82
	EOS#	10 ⁹ /L	0.05	± 0.05	0.00	-	0.10	0.12	± 0.12	0.00	-	0.24	0.20	± 0.20	0.00	-	0.40
	BAS#	10 ⁹ /L	0.01	± 0.01	0.00	-	0.02	0.04	± 0.04	0.00	-	0.08	0.10	± 0.10	0.00	-	0.20
	RBC	10 ¹² /L	2.36	± 0.18	2.18	-	2.54	4.58	± 0.24	4.34	-	4.82	5.66	± 0.35	5.31	-	6.01
	HGB	g/L	58	± 4	54	-	62	129	± 6	123	-	135	181	± 8	173	-	189
	MCV	fL	76.0	± 5.0	71.0	-	81.0	85.5	± 5.0	80.5	-	90.5	96.5	± 5.0	91.5	-	101.5
	HCT	L/L	0.179	± 0.020	0.159	-	0.199	0.392	± 0.030	0.362	-	0.422	0.546	± 0.035	0.511	-	0.581
	MCH	pg	24.6	± 2.5	22.1	-	27.1	28.2	± 2.5	25.7	-	30.7	32.0	± 2.5	29.5	-	34.5
	MCHC	g/L	323	± 30	293	-	353	329	± 30	299	-	359	331	± 30	301	-	361
	RDW-CV	%	16.0	± 3.0	13.0	-	19.0	15.0	± 3.0	12.0	-	18.0	13.5	± 3.0	10.5	-	16.5
	RDW-SD	fL	54.5	± 10.0	44.5	-	64.5	52.0	± 10.0	42.0	-	62.0	53.0	± 10.0	43.0	-	63.0
	PLT	10 ⁹ /L	83	± 20	63	-	103	236	± 45	191	-	281	439	± 65	374	-	504
	MPV	fL	10.0	± 3.0	7.0	-	13.0	9.8	± 3.0	6.8	-	12.8	9.9	± 3.0	6.9	-	12.9
PDW	/	17.0	± 4.0	13.0	-	21.0	16.0	± 3.0	13.0	-	19.0	15.5	± 3.0	12.5	-	18.5	
PCT	%	0.085	± 0.050	0.035	-	0.135	0.250	± 0.100	0.150	-	0.350	0.425	± 0.200	0.225	-	0.625	
P-LCR	%	17.0	± 10.0	7.0	-	27.0	19.0	± 10.0	9.0	-	29.0	19.5	± 10.0	9.5	-	29.5	
PLCC	10 ⁹ /L	14	± 10	4	-	24	45	± 25	20	-	70	86	± 35	51	-	121	

Remarks: These parameters values should be used as a reference only.

DIRUI INDUSTRIAL CO.,LTD.

95 Yunhe Street, New & High Tech.
Development Zone Changchun, Jilin 130012, P. R. China
Tel: +86 (431) 85100409 Fax: +86 (431) 85172581
E-mail: dirui@dirui.com.cn Http://www.dirui.com.cn



DIRUI BF-6900 CHECK ASSAY SHEET

LOT: 2411057

Exp.date: 2025-01-05

++

MODE	Parameter		Level:1				Level:2				Level:3						
			Mean	Limit	Range		Mean	Limit	Range		Mean	Limit	Range				
Open	WBC	10 ⁹ /L	2.50	± 0.50	2.00	-	3.00	8.00	± 1.00	7.00	-	9.00	20.30	± 2.50	17.80	-	22.80
	NEU%	%	68.0	± 12.0	56.0	-	80.0	68.0	± 12.0	56.0	-	80.0	87.5	± 12.0	75.5	-	99.5
	LYM%	%	23.0	± 10.0	13.0	-	33.0	23.0	± 10.0	13.0	-	33.0	9.0	± 9.0	0.0	-	18.0
	MON%	%	7.5	± 7.5	0.0	-	15.0	7.5	± 7.5	0.0	-	15.0	2.5	± 2.5	0.0	-	5.0
	EOS%	%	1.0	± 1.0	0.0	-	2.0	1.0	± 1.0	0.0	-	2.0	0.5	± 0.5	0.0	-	1.0
	BAS%	%	0.5	± 0.5	0.0	-	1.0	0.5	± 0.5	0.0	-	1.0	0.5	± 0.5	0.0	-	1.0
	NEU#	10 ⁹ /L	1.70	± 0.30	1.40	-	2.00	5.44	± 0.96	4.48	-	6.40	17.76	± 2.44	15.32	-	20.20
	LYM#	10 ⁹ /L	0.58	± 0.26	0.32	-	0.84	1.84	± 0.80	1.04	-	2.64	1.83	± 1.83	0.00	-	3.66
	MON#	10 ⁹ /L	0.19	± 0.19	0.00	-	0.38	0.60	± 0.60	0.00	-	1.20	0.51	± 0.51	0.00	-	1.02
	EOS#	10 ⁹ /L	0.03	± 0.03	0.00	-	0.06	0.08	± 0.08	0.00	-	0.16	0.10	± 0.10	0.00	-	0.20
	BAS#	10 ⁹ /L	0.01	± 0.01	0.00	-	0.02	0.04	± 0.04	0.00	-	0.08	0.10	± 0.10	0.00	-	0.20
	RBC	10 ¹² /L	2.21	± 0.18	2.03	-	2.39	4.45	± 0.24	4.21	-	4.69	5.60	± 0.35	5.25	-	5.95
	HGB	g/L	59	± 4	55	-	63	127	± 6	121	-	133	176	± 8	168	-	184
	MCV	fL	79.0	± 5.0	74.0	-	84.0	91.0	± 5.0	86.0	-	96.0	102.0	± 5.0	97.0	-	107.0
	HCT	L/L	0.175	± 0.020	0.155	-	0.195	0.405	± 0.030	0.375	-	0.435	0.571	± 0.035	0.536	-	0.606
	MCH	pg	26.7	± 2.5	24.2	-	29.2	28.5	± 2.5	26.0	-	31.0	31.4	± 2.5	28.9	-	33.9
	MCHC	g/L	338	± 30	308	-	368	314	± 30	284	-	344	308	± 30	278	-	338
	RDW-CV	%	13.5	± 3.0	10.5	-	16.5	12.0	± 3.0	9.0	-	15.0	11.5	± 3.0	8.5	-	14.5
	RDW-SD	fL	38.5	± 10.0	28.5	-	48.5	41.0	± 10.0	31.0	-	51.0	44.0	± 10.0	34.0	-	54.0
	PLT	10 ⁹ /L	84	± 20	64	-	104	243	± 45	198	-	288	455	± 65	390	-	520
MPV	fL	9.5	± 3.0	6.5	-	12.5	9.5	± 3.0	6.5	-	12.5	9.4	± 3.0	6.4	-	12.4	
PDW	/	11.5	± 3.0	8.5	-	14.5	11.0	± 3.0	8.0	-	14.0	11.0	± 3.0	8.0	-	14.0	
PCT	%	0.080	± 0.050	0.030	-	0.130	0.225	± 0.100	0.125	-	0.325	0.440	± 0.200	0.240	-	0.640	
P-LCR	%	20.0	± 10.0	10.0	-	30.0	19.0	± 10.0	9.0	-	29.0	20.0	± 10.0	10.0	-	30.0	
PLCC	10 ⁹ /L	17	± 10	7	-	27	46	± 25	21	-	71	91	± 35	56	-	126	

Remarks: These parameters values should be used as a reference only.

DIRUI INDUSTRIAL CO.,LTD.

95 Yunhe Street, New & High Tech.
 Development Zone Changchun, Jilin 130012, P. R. China
 Tel: +86 (431) 85100409 Fax: +86 (431) 85172581
 E-mail: dirui@dirui.com.cn Http://www.dirui.com.cn